



Protect



Suburban



Roads



Buildings

PROTECTION AND REPAIR > SURFACE PROTECTION

ALUPAINT GS

« Aluminium anti-corrosion paint for renovating metal structures and steel showing altered galvanisation. »

ADVANTAGES

> USE

- Renovates slides, railings and any metal parts with rust, graffiti or galvanisation defects
- Maintains and protects steel against the development of corrosion
- Its covering power effectively masks traces of graffiti
- Highly liquid paint for applying a low product coverage rate
- Waterproof and water-repellent paint

> INSTALLATION

- Ready-to-use product, easy to use by brush or spray
- A dedicated spray trolley can be used to increase application yield (contact us)
- Excellent adhesion for primerless application
- Very fast drying, minimising disruption during work operations
- Sakapo® specific packaging facilitates waste management and reduces costs

SOCIAL AND ENVIRONMENTAL BENEFITS

- **WASTE REDUCTION**
Sakapo® reduces the weight of hazardous waste by 65
- **MADE IN FRANCE**
Made in the Île-de-France region

AXIMUM



MADE IN
FRANCE



TECHNICAL CHARACTERISTICS

- Single-component acrylic paint based on aluminium pigments and solvents
- Density: 1.04kg/l
- Consistency: fluid
- Packaging: 25kg net metal buckets fitted with Sakapo
- Colour: aluminium

Other colours: contact us



IMPLEMENTATION

- Surface: galvanised steel
- Mix the product well with an electric mixer before use
- Apply to a clean, dry surface free of all loose matter, grease or corrosion
- High-pressure cleaning or burning of impurities is recommended
- Use in the open air or in a well-ventilated area.
- Apply with a brush, low-pressure or airless spray gun, or dedicated application trolley.
- Apply in one or two coats, allowing to dry thoroughly between each coat
- Surface temperature limits: $5^{\circ}\text{C} < T < 40^{\circ}\text{C}$
- Maximum humidity: 80%



CONSUMPTION	Application in layers
Product rate	150 to 175g/m ²
Yield	6 m ² /kg
Drying time	5 to 10min

NB: Comply with the consumption indications, as any excess coverage rate this can affect the quality of the coating



SAFETY - STORAGE

- Flammable product for professional use
- Storage: in a dry, well-ventilated place, away from frost, sunlight and any source of heat or sparks
- Shelf life: 12 months from date of manufacture, in unopened original packaging
- Soiled packaging and cleaning and rinsing products are waste to be treated in accordance with current regulations