



Clean



Work sites

PRIMER AND THINNER > CLEANER

# BITUBIO'CLEAN & BITUBIO'PROTECT



Cleaners for cleaning and protecting surfaces (machines, tools, equipment, PPE, etc.) contaminated by bituminous products or by-products, on site or in workshops. >>



Before/After

## ADVANTAGES

### > USES

- The Bitubio range protects and facilitates the maintenance of equipment used on site and in workshops without damaging it
- Bitubio'Protect: preventive product, used to preserve machinery by creating a protective layer that limits bitumen adhesion; for use on site.
- Bitubio'Clean: curative product intended for cleaning tools and machinery in the workshop; effective for quickly removing bitumen, even if heavily encrusted.

### > INSTALLATION

- Versatility of application: products can be used down to -10 °C and can be applied to hot surfaces (maximum 160 °C)
- No bad smell on application
- Easy to spray: low viscosity
- Various packaging options
- Preparations classified as harmless for users

## SOCIAL AND ENVIRONMENTAL BENEFITS

- BIO-SOURCED COMPONENTS  
Biodegradable products formulated from vegetable oils
- MADE IN FRANCE  
Made in the Hauts-de-France region



MADE IN FRANCE

# BITUBIO'CLEAN & BITUBIO'PROTECT



## TECHNICAL CHARACTERISTICS

- Preparations based on vegetable oil and vegetable oil methyl esters
- Density: 0.9 kg/L
- Closed cup flash point: > 180 °C
- Open cup flash point: > 200 °C
- Freezing point: < -20 °C
- Packaging: 25-litre drum or 1,000-litre IBC



## APPLICATION

### > CONDITIONS FOR USE

|                                     | BITUBIO'CLEAN                                                                                                                                                                                              | BITUBIO'PROTECT                                                                                                                               |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Protection of supports              | Non-optimal use                                                                                                                                                                                            | Spray the pure product on the entire surface of the equipment to be protected (machine, tools, PPE, etc.)                                     |
| Thin-film bitumen removal           | Spray the pure product on the area to be cleaned<br>Leave for 30 minutes<br>Rinse with pressurised water                                                                                                   | Spray the pure product on the area to be cleaned<br>Leave for 30 minutes<br>Rinse with pressurised water<br>Repeat as many times as necessary |
| Severe incrustation bitumen removal | Spray the pure product on the area to be cleaned<br>Leave for 5 minutes and then brush<br>Respray the product<br>Leave for 30 minutes<br>Rinse with pressurised water<br>Repeat as many times as necessary | Non-optimal use                                                                                                                               |

### > MATERIAL

- Application with a chemical-resistant sprayer
- Rinsing with water using a high-pressure washer, preferably with hot water

### > PRECAUTIONS FOR USE

- Prior to any application, test on a masked area to check the compatibility
- Use suitable personal protective equipment defined in the Safety Data Sheet
- Do not use on a surface where the temperature exceeds 160 °C
- Preferably use a containment system to collect bituminous residues
- On site, spray superficially to avoid drips; product application on asphalt may cause marking, discoloration, or even its destruction and subsequent stripping.



## SAFETY - STORAGE

- Product for professional use
- Store in a dry, ventilated place, away from frost, sunlight or any source of heat or sparks
- Conservation: 12 months from date of manufacture if original packaging unopened
- Dirty packaging, cleaning and rinsing products are forms of waste to be processed according to current regulations
- See Safety Data Sheet available at [www.quickfds.fr](http://www.quickfds.fr)



AXIMUM INDUSTRIE  
5, rue du Quai de Débarquement - 76100 ROUEN - France  
[aximum.com](http://aximum.com)